




# BEARING-THAILAND CO.,LTD

## TYPE TS



## Timken 18790 Bearing

Bearing No. 18790

Series	18700
Cone Part Number	18790
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>	21400 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup>	5550 lbf
d	2 in
B - Cone Width	0.6875 in
R - Cone Backface To Clear Radius <sup>3</sup>	0.14 in
da - Cone Frontface Backing Diameter	2.2 in
db - Cone Backface Backing Diameter	2.44 in
Ab - Cage-Cone Frontface Clearance	0.09 in
Aa - Cage-Cone Backface Clearance	0.02 in
a - Effective Center Location <sup>4</sup>	-0.03 in
C90 - Dynamic Radial Rating (90 million revolutions) <sup>5</sup>	3190 lbf
C1 - Dynamic Radial Rating (1 million revolutions) <sup>6</sup>	12300 lbf
C0 - Static Radial Rating	15200 lbf

18790 Bearing 2D drawings and 3D CAD models



## BEARING-THAILAND CO.,LTD

$C_{a90}$ - Dynamic Thrust Rating (90 million revolutions) <sup>7</sup>	2210 lbf
K - Factor <sup>8</sup>	1.44
G1 - Heat Generation Factor (Roller-Raceway)	28.6
G2 - Heat Generation Factor (Rib-Roller End)	21.5
Cg - Geometry Factor	0.0789